Class Rule Changes

International RS Aero Association Effective date: 2024-05(May)-13 Status: Approved



Amendment One

C.6.1.3 MODIFICATIONS

ADD NEW:

(ae) One single mounting line with a foot stirrup formed at one end (which may include plastic tubing) may be attached to the toe strap at the stern for the Crew to use to enter over the stern from the water, but not to be used otherwise. Shock cord may be used to retain the line when not in use.

Amendment Two

C.10 SAILS

C 10.4 MAINSAIL

(b) NATIONAL FLAGS

OLD:

- (i) Where stipulated in the NOR or SI, or when racing in any Class World Championship or Continental Championship, all Boats shall display the national flag of the **crew** attached a minimum of 60mm and maximum of 150mm below the national letters and also from the leach (see the relevant area shown in the drawing in Annex 2 below). The national flag is optional at all other events.
- (ii) Flags shall only be ordered and purchased through the ICA and shall not be trimmed or cut.

Amend to read:

- (i) Where stipulated in the NOR or SI, or when racing in any Class World Championship or Continental Championship, all Boats shall display the national flag of the **crew** on its mainsail.
- (ii) The flag shall be a minimum of 60mm and maximum of 150mm below the national letters and also from the leach (see the relevant area shown in the drawing in Annex 2 below). The national flag is optional at all other events.
- (iii) Flags shall only be ordered and purchased through the ICA and shall not be trimmed or cut.